



CorePro Glass LED bulbs



CorePro LEDBulb7-60W E27 A60 840 FR G

CorePro, LEDbulb, A60, 60 W, E27, 4000 K, 806 lm, CRI 80, 15000 hour(s), Glass

CorePro, LEDbulb, A60, 60 W, E27, 4000 K, 806 lm, CRI 80, 15000 hour(s), Glass, 115.00 lm/W, EEL E, PF 0.51, Beam angle 300 degree(s), RG1, IP20, SVM 0.4, PstLM 1

Product data

General Information	
Cap-Base	E27
Nominal lifetime	15,000 hour(s)
Switching Cycle	20,000
Lighting Technology	LEDbulb
Flux measurement reference	Sphere
Warranty period	2 years
Light Technical	
Color Code	840 [CCT of 4000K]
Beam Angle (Nom)	300 degree(s)
Luminous Flux	806 lm
Color Designation	Cool White (CW)
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	115.00 lm/W
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %


Photobiological safety according to EN 62471	RG1
Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	7 W
Lamp Current (Nom)	60 mA
Wattage Equivalent	60 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.51
Voltage (Nom)	220-240 V
Temperature	
T-Case Maximum (Nom)	50 °C
Controls and Dimming	
Dimmable	No

CorePro Glass LED bulbs

Mechanical and Housing	
Bulb Finish	Frosted
Bulb Material	Glass
Bulb Shape	A60
Net Weight (Piece)	0.030 kg
Approval and Application	
Energy Efficiency Class	E
Energy Consumption kWh/1000 h	7 kWh
EPREL Registration Number	1825141
CE mark	Yes
EU RoHS compliant	Yes
EyeComfort	Yes
Flickering value (PstLM) - Flickering value as per EN 61000-3-3	1
Stroboscopic effect visibility measure (SVM)	0.4
Ambient temperature range	-20 to +45 °C


Application Conditions	
can it be used in closed luminaires	No
Wireless Technology	Not applicable
Product Data	
Order product name	CorePro LEDBulb7-60W E27 A60 840 FR G
Full product name	CorePro LEDBulb7-60W E27 A60 840 FR G
Full product code	871951437751600
Order code	929001323592
Material Nr. (12NC)	929001323592
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8719514377516
Numerator - Packs per outer box	10
EAN/UPC - Case	8719514377523

Dimensional drawing




Product	D	C
CorePro LEDBulb7-60W E27 A60 840 FR G	60 mm	106 mm

Photometric data




Light Distribution Diagram - CorePro LEDBulb7-60W E27 A60 840 FR G



General uniform lighting - CorePro LEDBulb7-60W E27 A60 840 FR G


CorePro Glass LED bulbs

Photometric data




Spectral Power Distribution Colour - CorePro LEDBulb7-60W E27 A60 840 FR G

Lifetime



Life Expectancy Diagram



Lumen Maintenance Diagram - CorePro LEDBulb7-60W E27 A60 840 FR G

