



CorePro LED capsule MV



CorePro LEDcapsule ND 4.8-60W G9 830

CorePro, LED, Capsule, 60 W, G9, 3000 K, 570 lm, CRI 80, 15000 hour(s), Plastic

CorePro, LED, Capsule, 60 W, G9, 3000 K, 570 lm, CRI 80, 15000 hour(s), Plastic, 118 lm/W, EEL E, PF 0.4, Beam angle 280 degree(s), RG1, IP20, SVM 0.4, PstLM 1.0

Product data

General Information	
Cap-Base	G9
Nominal lifetime	15,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
Flux measurement reference	Sphere
Warranty period	2 years
Light Technical	
Color Code	830 [CCT of 3000K]
Beam Angle (Nom)	280 degree(s)
Luminous Flux	570 lm
Color Designation	White (WH)
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	118 lm/W
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %

Photobiological safety according to EN 62471	RG1
Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	4.8 W
Lamp Current (Nom)	44 mA
Wattage Equivalent	60 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.4
Voltage (Nom)	220-240 V
Temperature	
T-Case Maximum (Nom)	99 °C
Controls and Dimming	
Dimmable	No

CorePro LED capsule MV

Mechanical and Housing	
Bulb Finish	Clear
Bulb Material	Plastic
Bulb Shape	Capsule
Net Weight (Piece)	0.012 kg
Approval and Application	
Energy Efficiency Class	E
Suitable For Accent Lighting	No
Energy Consumption kWh/1000 h	5 kWh
EPREL Registration Number	397600
CE mark	Yes
EU RoHS compliant	Yes
EyeComfort	Yes
Flickering value (PstLM) - Flickering value as per EN 61000-3-3	1.0
Stroboscopic effect visibility measure (SVM)	0.4
Ambient temperature range	-20 to +35 °C

Application Conditions	
can it be used in closed luminaires	No
Wireless Technology	Not applicable
Product Data	
Order product name	CorePro LEDcapsule ND 4.8-60W G9 830
Full product name	CorePro LEDcapsule ND 4.8-60W G9 830
Full product code	871869965818200
Order code	929002059802
Material Nr. (12NC)	929002059802
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718699658182
Numerator - Packs per outer box	12
EAN/UPC - Case	8718699658199

Photometric data

Spectral Power Distribution Colour - CorePro LEDcapsule ND 4.8-60W G9 830

Light Distribution Diagram - CorePro LEDcapsule ND 4.8-60W G9 830

