



MASTER VALUE LED spot MV



MAS LED spot VLE D 2.8-35W GU10 927 60D

MASTER Value, LEDspot, PAR16, 35 W, GU10, 2700 K, 270 lm, CRI 90, 25000 hour(s), Glass

MASTER Value, LEDspot, PAR16, 35 W, GU10, 2700 K, 270 lm, CRI 90, 25000 hour(s), Glass, 96 lm/W, EEL E, PF 0.55, Beam angle 60 degree(s), RG1, IP20, SVM 0.4, PstLM 1

Warnings and Safety

- Operating temperature range is between -20° C and 45° C ambient
- Only to apply in dry or damp locations and most of open fixtures with lamp-holders that offer sufficient space (10 mm free air space)
- Not intended for use with emergency light fixtures or exit lights

Product data

General Information	
Cap-Base	GU10
Nominal lifetime	25,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LEDspot
Flux measurement reference	Narrow Cone
Warranty period	5 years
Light Technical	
Color Code	927 [CCT of 2700K]
Beam Angle (Nom)	60 degree(s)
Luminous Flux	270 lm

Luminous Intensity (Nom)	300 cd
Color Designation	Warm White (WW)
Correlated Color Temperature (Nom)	2700 K
Luminous Efficacy (rated) (Nom)	96 lm/W
Color Consistency	<6
Color rendering index (CRI)	90
LLMF At End Of Nominal Lifetime (Nom)	70 %
Luminous Flux in 90° Cone (Rated)	270 lm
Photobiological safety according to EN 62471	RG1

Operating and Electrical	
Input Frequency	50 to 60 Hz

MASTER VALUE LED spot MV

Power Consumption	2.8 W
Lamp Current (Nom)	21 mA
Wattage Equivalent	35 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.55
Voltage (Nom)	220-240 V

Temperature

T-Case Maximum (Nom)	50 °C
----------------------	-------

Controls and Dimming

Dimmable	Only with specific dimmers
----------	----------------------------

Mechanical and Housing

Bulb Finish	Clear
Bulb Material	Glass
Bulb Shape	PAR16
Net Weight (Piece)	0.041 kg

Approval and Application

Energy Efficiency Class	E
Suitable For Accent Lighting	Yes
Energy Consumption kWh/1000 h	3 kWh
EPREL Registration Number	2150468
CE mark	Yes

EU RoHS compliant	Yes
EyeComfort	Yes
Flickering value (PstLM) - Flickering value as per EN 61000-3-3	1
Stroboscopic effect visibility measure (SVM)	0.4
Ambient temperature range	-20 to +45 °C


Application Conditions

can it be used in closed luminaires	No
Wireless Technology	Not applicable

Product Data

Order product name	MAS LED spot VLE D 2.8-35W GU10 927 60D
Full product name	MAS LED spot VLE D 2.8-35W GU10 927 60D
Full product code	872016939916700
Order code	929004247602
Material Nr. (12NC)	929004247602
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169399167
Numerator - Packs per outer box	10
EAN/UPC - Case	8720169399174



Dimensional drawing



Product	D	C
MAS LED spot VLE D 2.8-35W GU10 927 60D	50 mm	54 mm


MASTER VALUE LED spot MV

Photometric data




Accent Lighting Spots - MAS LED spot VLE D 2.8-35W GU10 927 60D

Light Distribution Diagram - MAS LED spot VLE D 2.8-35W GU10 927 60D




Spectral Power Distribution Colour - MAS LED spot VLE D 2.8-35W GU10 927 60D

Lifetime



Life Expectancy Diagram



Lumen Maintenance Diagram - MAS LED spot VLE D 2.8-35W GU10 927 60D

MASTER VALUE LED spot MV

